



# Basswood Timber has been the mainstay of materials in the manufacture of Plantation Shutters for the last 10-15 years.

The raw material is kiln dried to a level best suited to our climate, following which numerous layers of primer, paint and top coat are applied. The Basswood Kimberley panels are reasonably light, they have a solid panel structure and hang true. They are not water or moisture resistant, however they are a good insulator.

Kimberley Shutters are available in a range of standard paint colours, with the stains being a favourite amongst interior designers looking to add warmth to a room. Without a doubt, Kimberley Shutters will be a focal point in any home,

- Approx. 7.7kg per m2.
- 5 Year Residential Warranty on the finish of the product.
- 15 year Workmanship Residential Warranty on the product
- Blades can close in both 'up' and 'down' directions
- Available in both Hidden Strip and Front Tilt Bar Operation
- Available in 63mm, 89mm blades and 114mm Blades
- 12 fashionable Standard Colours are available as standard which include 8 Paint Finishes and 5 Stain Finishes.
- Custom Paint colours available. Orders for custom colours require a sample – to correctly colour match we recommend a piece of cardboard painted (NOT a paint store sample swatch card).



\*Please refer to the manual for more in depth information. All sizes given on this form are correct, and over-ride any sizes listed in the product manual prior to this date V.190517. ). Note panels may require a lift to sit inside the frame, especially PVC, Double Hinged or wider panels. Use of the under panel leveller will ensure closed panels remain square following installation.

## HINGED SHUTTERS

- Wide Range of Frames available
- Minimum width 250mm, minimum height 350mm.
- Maximum width 950mm, Maximum Height 3000mm
- Maximum double hinged panel (eg LL, RR or LLRR) is 600mm per panel. Height of the panels must be greater than the width of two panels.
- Mid Rail required for heights over 1800mm, with a second mid rail for heights over 2400mm.

#### **SLIDING SHUTTERS**

- Maximum single panel width is 950mm.
- Panels exceeding 950mm can be made using "Combo Panels" – 2 panels hinged together to slide as one.
- Maximum panel height is 3000mm
- Mid Rail required for any panels over 1800mm. Two mid rails for panels over 2400mm.
- Available as 'Sliding Open' or 'Sliding Closed'
- Supplied with 140mm Fascia, which can be cut to suit onsite if the fascia will be fully reveal fitted
- We always recommend the use of bottom tracks for sliding shutters.

#### TRACK BIFOLD SHUTTERS

- Maximum single panel width is 700mm.
- Maximum panel height is 2400mm
- We recommend a maximum of 4 panels in a single direction
- Surface mount tracks, or tracks recessed into bottom frames are required for warranty
- Mid Rail required for any panels over 1800mm. Two mid rails for panels over 2400.
- Supplied with a 140mm Fascia, which can be cut to suit onsite if the fascia will be fully reveal fitted

### For Sales enquiries, please call Frank Bonacci

P: 0400 070 420

E: frank@artexshutters.com.au

Postal: 30 Lucknow Crescent, Thomastown VIC 3074 Phone: (03) 9462 2277 Fax: (03) 9462 2206



www.artexshutters.com.au